



Portland, TN Equipment Info

Equipment specification items	Slitter	Slitter
Year of manufacture	1990	1994
Manufacturer	Braner	Braner
Description of commodities	HR,CR, GA, GALV, Stainless, Pre-Paint, Motor Lam, Aluminum	HR,CR,GA, EG/GI, Aluminized, Aluminum
Tensile of strength (Mga)	1080	1080
Thickness of material (mm)	0.457mm ~ 3.42mm	0.457mm ~ 3.42mm
Min. width MC (mm)	200	200
Max. width MC (mm)	1828 mm	1828 mm
Max. coil weight (MT)	23.6	23.6
Coil ID (mm)	508 * 610	508 * 610
Coil OD(mm)	1,828	2,032
Min. slit width (mm)	30	30
No. of slitting (strip)	22, depending gauge	6
Tension unit type	Tension Pad-Tension Roll	Tension Pad
Cutting tolerance (mm)	+/- 0.13	+/- 0.13
Cutting type	Single and Double loop	Single / Double loop / Pull Thru
Line Speed (Ft/Min) or (SPM)	600	600
Leveler formation	4-High Leveler	
Monthly Capacity MT or SPM	10,000 MT	15,000 MT
Remarks & Characteristic	Gamma Gauge Reader Downender Packaging Line Inspection/Mapping Capable	Gamma Gauge Reader Inspection/Mapping Capable